





<p>Descriptions:</p> <ul style="list-style-type: none"> •Voltage available in DC12V •Nos. of LED: 37pcs of 5mm LED <p>Application:</p> <ul style="list-style-type: none"> •Channel letter signs •Indirect accent décor light •Large area back lighting •Under counter light •Decorate building's contour •Substitute neon light 	<p>Photo</p> 	<p>Outline Dimension</p> 	<p>Circuit Diagram</p>  <p>Unit : mm</p>
--	---	---	--

Typical Performance (Ta=25°C)

Items	Symbol	Min.	Typ.	Max.	Units
LED Module Power	Pm		3.1	5.5	w
Input Voltage(DC)	Vi		12	14	V
Input Current	If		260	390	mA
Beam Pattern	BP		15		Deg
Operating Temperature	Topr	-30		85	°C
Storage Temperature	Tstg	-40		100	°C
Length of PCB	Lmod.		609.6		mm



Device Selection Guide

Module No.	Color	Wavelength(Typ.)	Intensity / Per LED(Typ.)
OSMY61K37GH-B5SA5111A	Blue	470±3nm	14400 mcd
OSMY61K37GH-G5DA5111A	Pure Green	525±3nm	30000 mcd
OSMY61K37GH-Y5PA5111A	Yellow	590±3nm	18000 mcd
OSMY61K37GH-O5PA5111A	Orange	605±3nm	30000 mcd
OSMY61K37GH-R5PA5111A	Red	625±3nm	18000 mcd
OSMY61K37GH-W5DK5111A	White	X=0.27;Y=0.28	40000 mcd
OSMY61K37GH-M5DK5111A	Warm White	X=0.45;Y=0.41	22000 mcd
OSMY61K37GH-K5DK5111A	Pink	X=0.45;Y=0.17	7000 mcd