


**■ Features**

- High Luminous LEDs
- 8mm Round Standard Directivity
- UV Resistant Epoxy
- Integral Current Limiting Resistor
- TTL Compatible (Requires No External Current Limiter With 12 Volt Supply)
- Cost Effective (Saves space and resistor cost)
- Water clear Type

**■ Applications**

- Status Indicators
- Other Lighting


**■ Outline Dimension**












**■ Absolute Maximum Rating (Ta=25°C)**

Item	Symbol	Value	Unit
DC Forward Voltage	V <sub>F</sub>	15	V
Reverse Voltage	V <sub>R</sub>	5	V
Power Dissipation	P <sub>D</sub>	225	mW
Operating Temperature	Topr	-30 ~ +85	°C
Storage Temperature	Tstg	-30 ~ +85	°C
Lead Soldering Temperature	Tsol	260°C/5sec	-

**■ Directivity**



**■ Electrical -Optical Characteristics (Ta=25°C)**

Part Number	Color			I <sub>F</sub> (mA)			I <sub>v</sub> (mcd)*			λD(nm)*			2θ1/2(deg)
				Min	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Typ.
				V <sub>F</sub> = 12V			V <sub>F</sub> = 12V						
OSW5DK8131A-12V	White	W		-	10	15	3000	4200	-	X=0.27, Y=0.28			30
OSM5DK8131A-12V	Warm White	M		-	10	15	2180	3000	-	X=0.45, Y=0.41			30
OSB5SA8131A-12V	Blue	B		-	10	15	1560	2180	-	465	470	475	30
OSG5DA8131A-12V	Pure Green	TG		-	10	15	3000	4200	-	520	525	530	30
OSY5RU8131A-12V	Yellow	Y		-	10	15	1120	1560	-	585	590	595	30
OSY5PA8131A-12V	Yellow	Y		-	10	15	2180	3000	-	585	590	595	30
OSO5JA8131A-12V	Orange	O		-	10	15	1120	1560	-	600	605	610	30
OSO5PA8131A-12V	Orange	O		-	10	15	2500	3500	-	600	605	610	30
OSR5RU8131A-12V	Red	R		-	10	15	1120	1560	-	620	625	630	30
OSR5PA8131A-12V	Red	R		-	10	15	2180	3000	-	620	625	630	30

\*1 Tolerance of measurements of chromaticity coordinate is ±10%

\*2 Tolerance of measurements of luminous intensity is ±15%

\*3 Tolerance of measurements of dominant wavelength is +1nm