


■Features

- High Radiant Power
- Super Energy Efficiency
- Long Lifetime Operation
- Superior UV Resistance

■Applications

- Night Vision
- Camera
- Outdoor/Indoor Applications

■Outline Dimension




■Absolute Maximum Rating

(Ta=25°C)

Item	Symbol	Value	Unit
DC Forward Current	I _F	400	mA
Pulse Forward Current#	I _{FP}	1750	mA
Reverse Voltage	V _R	5	V
Power Dissipation	P _D	0.8	mW
Operating Temperature	T _{opr}	-30 ~ +85	°C
Storage Temperature	T _{stg}	-40 ~ +100	°C
Lead Soldering Temperature	T _{sol}	260°C/5sec	-

■Directivity



#Pulse width Max.10ms Duty ratio max 1/10

■Electrical –Optical Characteristics

(Ta=25°C)

Item	Symbo	Condition	Min.	Typ.	Max.	Unit
DC Forward Voltage*1	V _F	I _F =350mA	-	1.65	2.0	V
DC Reverse Current	I _R	V _R =5V	-	-	10	μA
Peak Wavelength*2	λ _p	I _F =350mA	-	940	-	nm
Radiant Power*3	P _O	I _F =350mA	80	90	-	mW
Radiant Intensity*4	E _e	I _F =350mA	140	150	-	mW/Sr
50% Power Angle	2θ _{1/2}	I _F =350mA	-	120	-	deg

*1 Tolerance of measurements of forward voltage is ±0.1V

*2 Tolerance of measurements of peak wavelength is +1nm

*3 Tolerance of measurements of Radiant Power is ±15%

*4 Tolerance of measurements of radiant intensity is +15%

Note: Don't drive at rated current more than 5s without heat sink for Xeon 0.6 emitter series.